

DC AXIAL FAN

JAMICON®

92X92X25 mm

SF0925-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%
- **IP68**
- **GR-487**

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF0925B1U	B	12	10.2~13.8	103.5	0.681	6000	0.84	10.08	0.90	53.5	133
SF0925B1S	B			96.4	0.603	5600	0.7	8.40	0.78	51.5	
SF0925B1H	B			85.7	0.485	5000	0.55	6.60	0.68	48.5	
SH0925B1M	B			77.1	0.397	4500	0.41	4.92	0.50	45.5	
SF0925B1L	B			68.0	0.326	4000	0.26	3.12	0.40	42.5	
SF0925B2U	B	24	20.4~27.6	103.5	0.681	6000	0.4	9.60	0.52	53.5	
SF0925B2S	B			96.4	0.603	5600	0.36	8.64	0.49	51.5	
SF0925B2H	B			85.7	0.485	5000	0.27	6.48	0.37	48.5	
SH0925B2M	B			77.1	0.397	4500	0.21	5.04	0.29	45.5	
SF0925B2L	B			68.0	0.326	4000	0.15	3.60	0.23	42.5	
SF0925B4U	B	48	40.8~55.2	103.5	0.681	6000	0.28	13.44	0.32	53.5	
SF0925B4S	B			96.4	0.603	5600	0.19	9.12	0.25	51.5	
SF0925B4H	B			85.7	0.485	5000	0.13	6.24	0.20	48.5	
SH0925B4M	B			77.1	0.397	4500	0.12	5.76	0.15	45.5	
SF0925B4L	B			68.0	0.326	4000	0.08	3.84	0.12	42.5	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

