

120x120x38mm

CF1238-33 Series



- **Frame:** Plastic Material UL 94-V0
- **Impeller:** Plastic Material UL 94-V0
- **Speed Range:** $\pm 10\%$
- **Operation Temperature(°C):** -25°C ~+70°C
- **Life Expectancy:** 70000hrs at 40 °C with 15~65%RH

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Power (Watt)	Noise (dBA)	Protection
CF12038B1S	B	110	50/60	209.00	1.00	4500	30.00	64.0	IP21 / IP55
CF12038B2S	B	220	50/60	209.00	1.00	4500	30.00	64.0	IP21 / IP55
CF12038B1H	B	110	50/60	185.70	0.89	4000	25.00	60.0	IP21 / IP55
CF12038B2H	B	220	50/60	185.70	0.89	4000	25.00	60.0	IP21 / IP55
CF12038B4L	B	110-220	50/60	139.30	0.66	3000	11.00	52.0	IP21 / IP55
CF12038B4E	B	110-220	50/60	116.00	0.55	2500	8.50	48.0	IP21 / IP55

Function: PWM / FG

All models could be customized or are not listed above, please contact us.

