

51x51x15mm

JB5015-11 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JB50155-S	B, N	5	4.25~5.75	4.29	0.864	6000	0.35	1.75	0.45	41.9	30
JB50155-H	B, N			3.48	0.534	5000	0.28	1.40	0.30	38.3	
JB50155-M	B, N			2.83	0.297	4000	0.20	1.00	0.20	32.8	
JB50151-T	B	12	10.2~13.8	5.72	1.887	8000	0.33	3.96	0.40	48.9	
JB50151-U	B			4.95	1.293	7000	0.25	3.00	0.35	45.7	
JB50151-S	B, N			4.29	0.864	6000	0.20	2.40	0.25	41.9	
JB50151-H	B, N			3.48	0.534	5000	0.13	1.56	0.15	38.3	
JB50151-M	B, N			2.83	0.297	4000	0.08	0.96	0.10	32.8	
JB50152-T	B	24	20.4~27.6	5.72	1.887	8000	0.15	3.60	0.20	48.9	
JB50152-U	B			4.95	1.293	7000	0.13	3.12	0.18	45.7	
JB50152-S	B, N			4.29	0.864	6000	0.10	2.40	0.15	41.9	
JB50152-H	B, N			3.48	0.534	5000	0.07	1.68	0.12	38.3	
JB50152-M	B, N			2.83	0.297	4000	0.06	1.44	0.08	32.8	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

