

DC AXIAL FAN

JAMICON®

60X60X25 mm

SF0625-33 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF0625B1X	B	12	10.2~13.8	49.02	0.870	10000	0.71	8.52	1.0	52.9	68
SF0625B1T	B			45.80	0.757	9200	0.52	6.24	0.80	51.6	
SF0625-1U	B			39.23	0.585	8000	0.37	4.44	0.55	46.5	
SF0625-1S	B			34.59	0.467	7000	0.26	3.12	0.35	43.6	
SF0625-1H	B			29.24	0.361	6000	0.19	2.28	0.25	38.9	
SF0625-1M	B, N, S			24.44	0.260	5000	0.12	1.44	0.18	33.1	
SF0625B2X	B	24	20.4~27.6	49.02	0.870	10000	0.37	8.88	0.5	52.9	
SF0625B2T	B			45.80	0.757	9200	0.28	6.72	0.4	51.6	
SF0625-2U	B			39.23	0.585	8000	0.19	4.56	0.3	46.5	
SF0625-2S	B			34.59	0.467	7000	0.14	3.36	0.20	43.6	
SF0625-2H	B			29.24	0.361	6000	0.10	2.40	0.15	38.9	
SF0625-2M	B, N, S			24.44	0.260	5000	0.07	1.68	0.10	33.1	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

