

DC AXIAL FAN

JAMICON®

40X40X10 mm

UF0410-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF0410-5T	B, N	5	4.25~5.75	10.79	0.361	9000	0.25	1.25	0.40	35.8	15
UF0410-5U				9.57	0.293	8000	0.18	0.90	0.25	32.5	
UF0410-5S				8.24	0.230	7000	0.14	0.70	0.20	28.5	
UF0410-5H				7.10	0.173	6000	0.10	0.50	0.15	24.4	
UF0410-5M				5.80	0.123	5000	0.07	0.35	0.10	19.2	
UF0410-5L				4.55	0.079	4000	0.05	0.25	0.08	14.3	
UF0410-1T	B, N	12	10.2~13.8	10.79	0.361	9000	0.09	1.08	0.20	35.8	
UF0410-1U				9.57	0.293	8000	0.08	0.96	0.18	32.5	
UF0410-1S				8.24	0.230	7000	0.07	0.84	0.15	28.5	
UF0410-1H				7.10	0.173	6000	0.05	0.60	0.12	24.4	
UF0410-1M				5.80	0.123	5000	0.04	0.48	0.08	19.2	
UF0410-1L				4.55	0.079	4000	0.03	0.36	0.05	14.3	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

