

80X80X38 mm

UF0838-33 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF0838-1T	B	12	10.2~13.8	148.86	3.729	15000	4.28	51.36	5.2	72.3	217
UF0838-1S				128.81	2.828	13000	2.93	35.16	3.5	68.7	
UF0838-1M				108.59	2.033	11000	1.88	22.56	2.5	64.3	
UF0838-1L				88.56	1.398	9000	1.28	15.36	2.0	59.1	
UF0838-2T	B	24	20.4~27.6	148.86	3.729	15000	2.27	54.48	2.8	72.3	
UF0838-2S				128.81	2.828	13000	1.34	32.16	1.8	68.7	
UF0838-2M				108.59	2.033	11000	1.04	24.96	1.2	64.3	
UF0838-2L				88.56	1.398	9000	0.75	18.00	1.0	59.1	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

