

80X80X25 mm

UF0825-22 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF0825-1X	B	12	10.2~13.8	97.46	1.090	9000	1.15	13.80	1.35	57.0	98
UF0825-1T	B			86.31	0.886	8000	0.82	9.84	0.95	54.1	
UF0825-1U	B			73.57	0.677	7000	0.58	6.96	0.70	50.4	
UF0825-1S	B			63.72	0.529	6000	0.41	4.92	0.50	46.7	
UF0825-1H	B,N			52.31	0.374	5000	0.27	3.24	0.35	41.5	
UF0825-1M	B,N			42.66	0.261	4000	0.18	2.16	0.25	35.6	
UF0825-2X	B	24	20.4~27.6	97.46	1.090	9000	0.57	13.68	0.65	57.0	
UF0825-2T	B			86.31	0.886	8000	0.42	10.08	0.50	54.1	
UF0825-2U	B			73.57	0.677	7000	0.31	7.44	0.35	50.4	
UF0825-2S	B			63.72	0.529	6000	0.20	4.80	0.25	46.7	
UF0825-2H	B,N			52.31	0.374	5000	0.14	3.36	0.20	41.5	
UF0825-2M	B,N			42.66	0.261	4000	0.11	2.64	0.15	35.6	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

