

120X120X38 mm

SF1238-55 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF1238B1T	B	12	10.2~13.8	252	1.228	6700	3.8	45.6	4.0	67	350
SF1238B1U	B			225	0.966	6000	2.6	31.2	3.0	63	
SF1238B1S	B			185	0.662	5000	1.6	19.2	1.8	58	
SF1238B1H	B			168	0.544	4500	1.2	14.4	1.4	56	
SF1238B2T	B	24	20.4~27.6	252	1.228	6700	1.9	45.6	2.0	67	
SF1238B2U	B			225	0.966	6000	1.3	31.2	1.5	63	
SF1238B2S	B			185	0.662	5000	0.8	19.2	0.9	58	
SF1238B2H	B			168	0.544	4500	0.6	14.4	0.7	56	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

