

120X120X38 mm

UF1238-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF1238B1T	B	12	10.2~13.8	261.4	1.488	6700	3.35	40.20	4.0	66.5	361
UF1238B1U	B			232.8	1.224	6000	2.40	28.80	3.0	64.4	
UF1238B1S	B			189.5	0.974	5000	1.28	15.36	1.8	60.1	
UF1238B1H	B			170.5	0.805	4500	0.97	11.64	1.4	57.5	
UF1238B2X	B	24	20.4~27.6	287.6	1.736	7500	2.30	55.20	2.8	69.5	
UF1238B2T	B			261.4	1.488	6700	1.53	36.72	2.0	66.5	
UF1238B2U	B			232.8	1.224	6000	1.05	25.20	1.5	64.4	
UF1238B2S	B			189.5	0.974	5000	0.65	15.60	0.9	60.1	
UF1238B2H	B			170.5	0.805	4500	0.45	10.80	0.7	57.5	
UF1238B4X	B	48	40.8~55.2	287.6	1.736	7500	1.10	52.80	1.4	69.5	
UF1238B4T	B			261.4	1.488	6700	0.80	38.40	1.0	66.5	
UF1238B4U	B			232.8	1.224	6000	0.58	27.84	0.8	64.4	
UF1238B4S	B			189.5	0.974	5000	0.32	15.36	0.6	60.1	
UF1238B4H	B			170.5	0.805	4500	0.25	12.00	0.4	57.5	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

