

120X120X25 mm

KF1225-SL Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$



SPECIFICATIONS											
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF1225-1SR	B, N	12	10.2 ~13.8	86.65	0.143	2600	0.30	3.60	0.35	37.6	118
KF1225-1HR	B, N			74.25	0.111	2200	0.30	3.60	0.35	32.7	
KF1225-1M	B, N			59.78	0.076	1800	0.19	2.28	0.20	28.3	
KF1225-1L	B, N			46.51	0.053	1500	0.13	1.56	0.14	23.0	
KF1225-1E	B, N			41.37	0.038	1200	0.07	0.84	0.09	18.8	
KF1225-1V	B, N			39.75	0.030	1000	0.06	0.72	0.07	15.3	
KF1225-2SR	B, N	24	20.4 ~27.6	86.65	0.143	2600	0.20	4.80	0.20	37.6	
KF1225-2HR	B, N			74.25	0.111	2200	0.18	4.32	0.20	32.7	
KF1225-2M	B, N			59.78	0.076	1800	0.12	2.88	0.13	28.3	
KF1225-2L	B, N			46.51	0.053	1500	0.08	1.92	0.09	23.0	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

