


92X92X38 mm

UF0938-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF0938B1U	B	12	10.2~13.8	156.04	2.941	11000	3.20	38.40	4.0	68.8	258
UF0938B1S	B			143.00	2.420	10000	2.45	29.40	3.0	65.3	
UF0938B1H	B			127.76	1.956	9000	1.75	21.00	2.3	63.9	
UF0938B1M	B			111.25	1.553	8000	1.25	15.00	1.8	60.8	
UF0938B1L	B			99.69	1.241	7000	0.90	10.80	1.3	58.4	
UF0938B2T	B	24	20.4~27.6	171.10	3.500	12000	2.35	56.40	3.0	71.4	
UF0938B2U	B			156.04	2.941	11000	1.55	37.20	2.0	68.8	
UF0938B2S	B			143.00	2.420	10000	1.15	27.60	1.5	65.3	
UF0938B2H	B			127.76	1.956	9000	0.85	20.40	1.2	63.9	
UF0938B2M	B			111.25	1.553	8000	0.60	14.40	0.9	60.8	
UF0938B2L	B			99.69	1.241	7000	0.45	10.80	0.7	58.4	
UF0938B4T	B	48	40.8~55.2	171.10	3.500	12000	0.95	45.60	1.5	71.4	
UF0938B4U	B			156.04	2.941	11000	0.80	38.40	1.2	68.8	
UF0938B4S	B			143.00	2.420	10000	0.60	28.80	1.0	65.3	
UF0938B4H	B			127.76	1.956	9000	0.42	20.20	0.8	63.9	
UF0938B4M	B			111.25	1.553	8000	0.38	18.20	0.6	60.8	
UF0938B4L	B			99.69	1.241	7000	0.22	10.60	0.4	58.4	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

