


# DC AXIAL FAN

JAMICON®

60X60X38 mm

UF0638-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

## SPECIFICATIONS

| Model     | Bearing | Rated Voltage (V) | Operating Voltage (V) | Air Flow (CFM) | Static Pressure (inchH <sub>2</sub> O) | Speed (R.P.M.) | Input Current (Amp) | Input Power (Watt) | Nominal Current (Amp) | Noise (dBA) | Weight (g) |
|-----------|---------|-------------------|-----------------------|----------------|----------------------------------------|----------------|---------------------|--------------------|-----------------------|-------------|------------|
| UF0638B1T | B       | 12                | 10.2 ~ 13.8           | 77.9           | 4.867                                  | 22000          | 2.69                | 32.28              | 3.5                   | 68.7        | 117        |
| UF0638B1U |         |                   |                       | 75.5           | 4.505                                  | 21000          | 2.19                | 26.28              | 2.8                   | 67.1        |            |
| UF0638B1S |         |                   |                       | 71.1           | 4.117                                  | 20000          | 1.90                | 22.8               | 2.5                   | 66.2        |            |
| UF0638B1H |         |                   |                       | 67.2           | 3.681                                  | 19000          | 1.59                | 19.08              | 2.0                   | 64.8        |            |
| UF0638B1M |         |                   |                       | 64.0           | 3.407                                  | 18000          | 1.37                | 16.44              | 1.7                   | 62.9        |            |
| UF0638B2T | B       | 24                | 20.4 ~ 27.6           | 77.9           | 4.867                                  | 22000          | 1.27                | 30.48              | 1.8                   | 68.7        |            |
| UF0638B2U |         |                   |                       | 75.5           | 4.505                                  | 21000          | 1.02                | 24.48              | 1.5                   | 67.1        |            |
| UF0638B2S |         |                   |                       | 71.1           | 4.117                                  | 20000          | 0.95                | 22.8               | 1.3                   | 66.2        |            |
| UF0638B2H |         |                   |                       | 67.2           | 3.681                                  | 19000          | 0.81                | 19.44              | 1.1                   | 64.8        |            |
| UF0638B2M |         |                   |                       | 64.0           | 3.407                                  | 18000          | 0.66                | 15.84              | 0.9                   | 62.9        |            |

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

