


60X60X25 mm

SF0625-56 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF0625B1X	B	12	10.2 ~ 13.8	44.68	0.954	10000	0.73	8.76	1.0	53.9	65
SF0625B1T	B			40.24	0.859	9200	0.55	6.60	0.80	52.1	
SF0625-1U	B, N			34.53	0.661	8000	0.35	4.20	0.55	49.0	
SF0625-1S	B, N			30.46	0.518	7000	0.25	3.00	0.35	44.6	
SF0625-1H	B, N			25.62	0.406	6000	0.17	2.04	0.25	40.9	
SF0625-1M	B, N			21.64	0.266	5000	0.11	1.32	0.18	35.3	
SF0625B2X	B	24	20.4 ~ 27.6	44.68	0.954	10000	0.40	9.60	0.5	53.9	
SF0625B2T	B			40.24	0.859	9200	0.30	7.20	0.4	52.1	
SF0625-2U	B, N			34.53	0.661	8000	0.21	5.04	0.3	49.0	
SF0625-2S	B, N			30.46	0.518	7000	0.15	3.60	0.20	44.6	
SF0625-2H	B, N			25.62	0.406	6000	0.10	2.40	0.15	40.9	
SF0625-2M	B, N			21.64	0.266	5000	0.06	1.44	0.10	35.3	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

