

DC AXIAL FAN

JAMICON®

40x40x20 mm

SF0420-11
SF0420-12 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF0420B1T	B	12	10.2~13.8	23.94	1.154	17000	0.75	9.00	0.80	55.8	30
SF0420B1U				22.82	1.034	16000	0.52	6.24	0.60	53.9	
SF0420B1S				19.88	0.787	14000	0.37	4.44	0.46	50.2	
SF0420B1H				16.48	0.583	12000	0.27	3.24	0.30	45.5	
SF0420B1M				13.54	0.414	10000	0.16	1.92	0.22	40.5	
SF0420-1L	B, N, H, S			9.88	0.228	8000	0.15	1.80	0.18	33.3	
SF0420-1E				8.50	0.169	6500	0.10	1.20	0.14	27.7	
SF0420-1V				5.71	0.099	5000	0.08	0.96	0.10	22.5	
SF0420B2T	B	24	20.4~27.6	23.94	1.154	17000	0.35	8.40	0.40	55.8	
SF0420B2U				22.82	1.034	16000	0.28	6.72	0.30	53.9	
SF0420B2S				19.88	0.787	14000	0.20	4.80	0.23	50.2	
SF0420B2H				16.48	0.583	12000	0.14	3.36	0.15	45.5	
SF0420B2M				13.54	0.414	10000	0.10	2.40	0.11	40.5	
SF0420-2L	B, N, H, S			9.88	0.228	8000	0.07	1.68	0.09	33.3	
SF0420-2E				8.50	0.169	6500	0.06	1.44	0.07	27.7	
SF0420-2V				5.71	0.099	5000	0.04	0.96	0.05	22.5	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

