

DC AXIAL FAN

JAMICON®

40X40X10 mm

KF0410-03
KF0410-08 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0410B5H-AO	B	5	4.25~5.75	8.09	0.187	7500	0.16	0.80	0.8	31.4	16
KF0410B5H				6.42	0.129	6000	0.13	0.65	0.8	26.4	
KF0410B5M				5.75	0.106	5400	0.09	0.45	0.5	24.4	
KF0410B5L				4.37	0.067	4200	0.07	0.35	0.4	19.9	
KF0410-5H	N,S			6.42	0.129	6000	0.20	1.00	1.2	26.4	
KF0410-5M				5.75	0.106	5400	0.10	0.50	0.8	24.4	
KF0410-5L				4.37	0.067	4200	0.08	0.40	0.6	19.9	
KF0410B1H-AO	B	12	10.2~13.8	8.09	0.187	7500	0.06	0.72	0.8	31.4	
KF0410B1H				6.42	0.129	6000	0.06	0.80	0.8	26.4	
KF0410B1M				5.75	0.106	5400	0.058	0.70	0.7	24.4	
KF0410B1L				4.37	0.067	4200	0.05	0.60	0.6	19.9	
KF0410-1H	N,S			6.42	0.129	6000	0.08	0.96	1.2	26.4	
KF0410-1M				5.75	0.106	5400	0.066	0.80	0.8	24.4	
KF0410-1L				4.37	0.067	4200	0.058	0.70	0.7	19.9	
KF0410B2S-AI	B	24	20.4~27.6	8.09	0.187	7500	0.058	1.40	1.4	31.4	
KF0410B2S				6.97	0.159	6600	0.05	1.20	1.4	29.3	
KF0410B2H				6.42	0.129	6000	0.05	1.20	1.2	26.4	
KF0410B2M				5.75	0.106	5400	0.04	0.96	1.0	24.4	
KF0410B2L				4.37	0.067	4200	0.03	0.72	0.8	19.9	
KF0410-2H	N,S			6.42	0.129	6000	0.05	1.20	1.2	26.4	
KF0410-2M				5.75	0.106	5400	0.04	0.96	1.0	24.4	
KF0410-2L				4.37	0.067	4200	0.03	0.72	0.8	19.9	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

