

DC AXIAL FAN

JAMICON®

60X60X15 mm

JF0615-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0615-5HR	B,N,S	5	4.25 ~ 5.75	15.45	0.165	4500	0.25	1.25	0.26	30.5	45
JF0615-5MR	B,N,S			13.58	0.140	4000	0.20	1.00	0.21	28.8	
JF0615-5L	B,N,S			11.86	0.107	3500	0.17	0.85	0.17	25.4	
JF0615-5E	B,N,S			9.82	0.081	3000	0.14	0.70	0.14	21.2	
JF0615-5V	B,N,S			8.39	0.059	2500	0.11	0.55	0.11	17.9	
JF0615B1UR	B	12	10.2 ~ 13.8	18.87	0.220	5500	0.15	1.80	0.16	37.5	
JF0615B1S	B			17.16	0.200	5000	0.14	1.68	0.15	33.7	
JF0615-1H	B,N,S			15.45	0.165	4500	0.13	1.56	0.17	30.5	
JF0615-1M	B,N,S			13.58	0.140	4000	0.12	1.44	0.15	28.8	
JF0615-1L	B,N,S			11.86	0.107	3500	0.10	1.20	0.12	25.4	
JF0615-1E	B,N,S	24	20.4 ~ 27.6	9.82	0.081	3000	0.08	0.96	0.09	21.2	
JF0615-1V	B,N,S			8.39	0.059	2500	0.07	0.84	0.07	17.9	
JF0615B2UR	B			18.87	0.220	5500	0.11	2.64	0.12	37.5	
JF0615B2S	B			17.16	0.200	5000	0.10	2.40	0.11	33.7	
JF0615-2H	B,N,S			15.45	0.165	4500	0.13	3.12	0.13	30.5	
JF0615-2M	B,N,S			13.58	0.140	4000	0.11	2.64	0.11	28.8	
JF0615-2L	B,N,S			11.86	0.107	3500	0.09	2.16	0.09	25.4	
JF0615-2E	B,N,S			9.82	0.081	3000	0.06	1.44	0.06	21.2	
JF0615-2V	B,N,S			8.39	0.059	2500	0.04	0.96	0.04	17.9	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

