

DC AXIAL FAN

JAMICON®

35X35X10 mm

KF0B10-01 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 15\%$



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0B10-5SR	B,N,S	5	4.25 ~ 5.75	7.32	0.159	9500	0.23	1.15	1.2	29.9	8.5
KF0B10-5HR				6.53	0.134	8500	0.21	1.05	1.1	26.3	
KF0B10-5MR				5.78	0.113	7500	0.14	0.70	0.8	24.5	
KF0B10-5LR				4.95	0.087	6500	0.09	0.45	0.5	20.7	
KF0B10-5ER				3.66	0.055	4800	0.07	0.35	0.4	15.0	
KF0B10-1SR		12	10.2 ~ 13.8	7.32	0.159	9500	0.13	1.56	1.7	29.9	
KF0B10-1HR				6.53	0.134	8500	0.10	1.20	1.2	26.3	
KF0B10-1MR				5.78	0.113	7500	0.08	0.96	1.0	24.5	
KF0B10-1LR				4.95	0.087	6500	0.06	0.72	0.8	20.7	
KF0B10-1ER				3.66	0.055	4800	0.05	0.60	0.6	15.0	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

