

120X120X25 mm

JA1225-0N Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : $\pm 10\%$
- **Impedance protected**

SPECIFICATIONS

Model	Bearing	Nominal Voltage (V)	Frequency (Hz)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Nominal Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
JA1225H1B0N	B	110 - 120	50	60.82	0.162	2250	0.18	18	39.4	325
			60	68.26	0.167	2500		15	42.5	
JA1225H1S0N	S		50	59.96	0.157	2200	0.18	18	39.2	
			60	65.49	0.151	2400		15	41.8	
JA1225H2B0N	B	220 - 240	50	60.82	0.162	2250	0.09	17	39.4	
			60	68.26	0.167	2500		15	42.5	
JA1225H2S0N	S		50	59.96	0.157	2200	0.09	17	39.2	
			60	65.49	0.151	2400		15	41.8	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / S= Sleeve bearing

