

DC AXIAL FAN

JAMICON®

140X140X25 mm

KF1425-11 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
KF1425B1TR	B	12	10.2 ~ 13.8	125.61	0.233	2800	0.54	6.48	0.65	46.4	176		
KF1425B1UR				112.14	0.193	2500	0.48	5.76	0.58	43.4			
KF1425B1SR				104.41	0.147	2300	0.41	4.92	0.49	40.0			
KF1425-1H	B,N,S			89.04	0.139	2000	0.28	3.36	0.34	36.2			
KF1425-1M				80.92	0.106	1800	0.20	2.40	0.24	32.6			
KF1425-1L				70.83	0.074	1600	0.15	1.80	0.18	29.7			
KF1425-1E				53.50	0.045	1200	0.08	0.96	0.10	21.1			
KF1425-1V				46.01	0.036	1000	0.06	0.72	0.07	17.1			

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

