

140X140X25 mm

JF1425-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1425B1UR	B	12	10.2~13.8	156.48	0.194	2400	0.68	8.16	0.80	45.60	220
JF1425B1SR				131.38	0.140	2100	0.48	5.76	0.60	41.70	
JF1425-1HR	B,N,S			113.56	0.104	1800	0.36	4.32	0.44	37.10	
JF1425-1M				93.16	0.080	1500	0.21	2.52	0.25	32.10	
JF1425-1L				73.95	0.047	1200	0.13	1.56	0.18	26.50	
JF1425-1E				53.92	0.030	900	0.07	0.84	0.11	20.40	
JF1425B2UR	B	24	20.4~27.6	156.48	0.194	2400	0.36	8.64	0.38	45.60	
JF1425B2SR				131.38	0.140	2100	0.24	5.76	0.26	41.70	
JF1425-2HR	B,N,S			113.56	0.104	1800	0.23	5.52	0.27	37.10	
JF1425-2M				93.16	0.080	1500	0.14	3.36	0.17	32.10	
JF1425-2L				73.95	0.047	1200	0.10	2.40	0.13	26.50	
JF1425-2E				53.92	0.030	900	0.06	1.44	0.09	20.40	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

