

120X120X38 mm

JF1238-19 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1238B1SR	B	12	10.2 ~ 13.8	135.8	0.356	3200	0.70	8.40	0.80	47.9	278
JF1238-1HR	B,N,S			118.7	0.281	2800	0.48	5.76	0.55	43.8	
JF1238-1MR	B,N,S			101.3	0.213	2400	0.32	3.96	0.38	39.1	
JF1238-1LR	B,N,S			84.5	0.155	2000	0.20	2.40	0.21	33.8	
JF1238-1ER	B,N,S			69.6	0.109	1700	0.10	1.20	0.11	29.6	
JF1238B2SR	B	24	20.4 ~ 27.6	135.8	0.356	3200	0.37	8.88	0.45	47.9	
JF1238-2HR	B,N,S			118.7	0.281	2800	0.31	7.44	0.32	43.8	
JF1238-2MR	B,N,S			101.3	0.213	2400	0.22	5.28	0.23	39.1	
JF1238-2LR	B,N,S			84.5	0.155	2000	0.13	3.12	0.14	33.8	
JF1238-2ER	B,N,S			69.6	0.109	1700	0.09	2.16	0.11	29.6	
JF1238B4SR	B	48	40.8 ~ 55.2	135.8	0.356	3200	0.20	9.60	0.22	47.9	
JF1238B4HR	B			118.7	0.281	2800	0.13	6.24	0.15	43.8	
JF1238B4MR	B			101.3	0.213	2400	0.09	4.32	0.11	39.1	
JF1238B4LR	B			84.5	0.155	2000	0.07	3.36	0.08	33.8	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

