

120X120X25 mm

KF1225-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF1225-1HR	B,N,H,S	12	10.2 ~ 13.8	80.49	0.141	2200	0.30	3.60	0.35	38.5	133
KF1225-1M				65.63	0.099	1800	0.19	2.28	0.20	32.5	
KF1225-1L				54.05	0.071	1500	0.13	1.56	0.14	27.4	
KF1225-1E				43.23	0.047	1200	0.07	0.84	0.09	21.4	
KF1225-1V				35.37	0.033	1000	0.06	0.72	0.07	15.5	
KF1225-2HR	B,N,H,S	24	20.4 ~ 27.6	80.49	0.141	2200	0.18	4.32	0.20	38.5	
KF1225-2M				65.63	0.099	1800	0.12	2.88	0.13	32.5	
KF1225-2L				54.05	0.071	1500	0.08	1.92	0.09	27.4	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

