

120X120X25 mm

JF1225-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1225B1URAB	B	12	10.2 ~ 13.8	111.36	0.340	3200	0.50	6.00	0.50	47.8	205
JF1225B1UR				100.50	0.269	3000	0.50	6.00	0.50	45.7	
JF1225B1SR				89.87	0.224	2700	0.37	4.44	0.37	42.8	
JF1225-1H	B,N,S			80.11	0.186	2400	0.25	3.00	0.30	39.5	
JF1225-1M	B,N,S			69.57	0.147	2100	0.20	2.40	0.25	36.3	
JF1225-1L	B,N,S			59.57	0.111	1800	0.14	1.68	0.20	32.4	
JF1225-1E	B,N,S			47.88	0.078	1500	0.10	1.20	0.12	27.4	
JF1225B2URAB	B			24	20.4~ 27.6	111.36	0.340	3200	0.28	6.72	
JF1225B2UR		100.50	0.269			3000	0.28	6.72	0.28	45.7	
JF1225B2SR		89.87	0.224			2700	0.21	5.04	0.21	42.8	
JF1225-2H	B,N,S	80.11	0.186			2400	0.20	4.80	0.25	39.5	
JF1225-2M	B,N,S	69.57	0.147			2100	0.14	3.36	0.20	36.3	
JF1225-2L	B,N,S	59.57	0.111			1800	0.11	2.64	0.15	32.4	
JF1225-2E	B,N,S	47.88	0.078			1500	0.08	1.92	0.10	27.4	
JF1225B4UR	B	48	40.8 ~ 55.2			100.50	0.269	3000	0.14	6.72	
JF1225B4SR				89.87	0.224	2700	0.12	5.76	0.12	42.8	
JF1225B4HR				80.11	0.186	2400	0.10	4.80	0.10	39.5	
JF1225B4MR				69.57	0.147	2100	0.08	3.84	0.08	36.3	
JF1225B4LR				59.57	0.111	1800	0.07	3.36	0.07	32.4	
JF1225B4ER				47.88	0.078	1500	0.06	2.88	0.06	27.4	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

