

DC AXIAL FAN

JAMICON®

92X92X25 mm

KF0925-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0925-1T	B	12	10.2~13.8	83.56	0.355	4400	0.48	5.76	0.54	48.5	100
KF0925-1U	B			72.92	0.293	4000	0.33	3.96	0.42	45.9	
KF0925-1S	B			60.14	0.200	3300	0.23	2.76	0.28	40.5	
KF0925-1H	B,N,S			53.00	0.160	2900	0.16	1.91	0.24	36.7	
KF0925-1M	B,N,S			47.80	0.130	2600	0.12	1.44	0.15	33.7	
KF0925-1L	B,N,S			42.00	0.100	2300	0.09	1.08	0.10	30.5	
KF0925-1E	B,N,S			33.28	0.070	1900	0.07	0.84	0.08	26.5	
KF0925-2T	B	24	20.4~27.6	83.56	0.355	4400	0.26	6.24	0.29	48.5	
KF0925-2U	B			72.92	0.293	4000	0.18	4.32	0.24	45.9	
KF0925-2S	B			60.14	0.200	3300	0.10	2.40	0.15	40.5	
KF0925-2H	B,N,S			53.00	0.160	2900	0.08	1.92	0.12	36.7	
KF0925-2M	B,N,S			47.80	0.130	2600	0.07	1.68	0.10	33.7	
KF0925-2L	B,N,S			42.00	0.100	2300	0.05	1.20	0.08	30.5	
KF0925-2E	B,N,S			33.28	0.070	1900	0.04	0.96	0.07	26.5	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

