

80X80X38 mm

JF0838-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0838B1S	B	12	10.2 ~ 13.8	90.38	0.795	6300	1.12	13.44	1.34	53.6	174
JF0838B1H				80.58	0.632	5700	0.95	11.40	1.14	51.9	
JF0838B2S	B	24	20.4~27.6	90.38	0.795	6300	0.60	14.40	0.72	53.6	
JF0838B2H				80.58	0.632	5700	0.52	12.48	0.62	51.9	
JF0838B4S	B	48	40.8~55.2	90.38	0.795	6300	0.33	15.84	0.40	53.6	
JF0838B4H				80.58	0.632	5700	0.27	12.96	0.32	51.9	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

