

DC AXIAL FAN

JAMICON®

80X80X38 mm

KF0838-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0838B1U	B	12	10.2 ~ 13.8	106.39	1.23	7000	1.50	18.00	2.20	60.30	188
KF0838B1S				90.85	0.96	6100	0.98	11.76	1.20	56.40	
KF0838B1H				75.79	0.62	5000	0.60	7.20	0.72	50.90	
KF0838B1M				61.29	0.47	4200	0.40	4.80	0.48	46.20	
KF0838B1L				52.55	0.34	3500	0.27	3.24	0.32	41.40	
KF0838B1E				35.93	0.17	2500	0.14	1.68	0.17	32.30	
KF0838B1V				28.36	0.11	2000	0.10	1.20	0.12	27.30	
KF0838B2U	B	24	20.4 ~ 27.6	106.39	1.23	7000	0.70	16.80	0.84	60.30	
KF0838B2S				90.85	0.96	6100	0.52	12.48	0.62	56.40	
KF0838B2H				75.79	0.62	5000	0.32	7.68	0.36	50.90	
KF0838B2M				61.29	0.47	4200	0.22	5.28	0.26	46.20	
KF0838B2L				52.55	0.34	3500	0.14	3.36	0.17	41.40	
KF0838B2E				35.93	0.17	2500	0.08	1.92	0.10	32.30	
KF0838B2V				28.36	0.11	2000	0.06	1.44	0.07	27.30	
KF0838B4U	B	48	40.8 ~ 55.2	106.39	1.23	7000	0.37	17.76	0.44	60.30	
KF0838B4S				90.85	0.96	6100	0.24	11.52	0.29	56.40	
KF0838B4H				75.79	0.62	5000	0.20	9.60	0.24	50.90	
KF0838B4M				61.29	0.47	4200	0.15	7.20	0.18	46.20	
KF0838B4L				52.55	0.34	3500	0.14	6.72	0.17	41.40	
KF0838B4E				35.93	0.17	2500	0.10	4.80	0.12	32.30	
KF0838B4V				28.36	0.11	2000	0.08	3.84	0.10	27.30	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

