

80X80X25 mm

JF0825-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0825B1UR	B	12	10.2 ~ 13.8	52.06	0.227	4000	0.37	4.44	0.37	40.0	70
JF0825-1SR	B,N,S			45.46	0.189	3500	0.26	3.12	0.26	35.8	
JF0825-1H	B,N,S			38.74	0.142	3000	0.19	2.28	0.19	31.0	
JF0825-1M	B,N,S			32.52	0.099	2500	0.13	1.56	0.15	27.8	
JF0825-1L	B,N,S			25.54	0.067	2000	0.09	1.08	0.10	22.2	
JF0825-1E	B,N,S			19.09	0.039	1500	0.06	0.72	0.06	15.9	
JF0825B2TR	B	24	20.4 ~ 27.6	57.84	0.272	4500	0.27	6.48	0.27	42.4	
JF0825B2UR	B			52.06	0.227	4000	0.21	5.04	0.21	40.0	
JF0825-2SR	B,N,S			45.46	0.189	3500	0.16	3.84	0.17	35.8	
JF0825-2H	B,N,S			38.74	0.142	3000	0.13	3.12	0.15	31.0	
JF0825-2M	B,N,S			32.52	0.099	2500	0.10	2.40	0.13	27.8	
JF0825-2L	B,N,S			25.54	0.067	2000	0.08	1.92	0.10	22.2	
JF0825-2E	B,N,S			19.09	0.039	1500	0.04	0.96	0.05	15.9	
JF0825B4SR	B	48	40.8 ~ 55.2	45.46	0.189	3500	0.10	4.80	0.10	35.8	
JF0825B4HR				38.74	0.142	3000	0.08	3.84	0.08	31.0	
JF0825B4MR				32.52	0.099	2500	0.06	2.88	0.06	27.8	
JF0825B4LR				25.54	0.067	2000	0.05	2.40	0.05	22.2	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

