

80X80X25 mm

KF0825-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
KF0825B1TR	B	12	10.2 ~ 13.8	57.28	0.38	4500	0.42	5.04	0.50	42.10	86		
KF0825B1UR				50.25	0.30	4000	0.29	3.48	0.35	39.00			
KF0825B1SR				43.97	0.23	3500	0.25	3.00	0.30	34.80			
KF0825-1H	B,N,H,S			37.40	0.17	3000	0.17	2.04	0.20	30.90			
KF0825-1M	B,N,H,S			30.60	0.12	2500	0.10	1.20	0.12	25.80			
KF0825-1L	B,N,H,S			24.20	0.08	2000	0.07	0.84	0.08	22.30			
KF0825-1E	B,N,H,S			18.44	0.05	1500	0.04	0.48	0.05	20.50			
KF0825B2UR	B			24	20.4 ~ 27.6	50.25	0.30	4000	0.17	4.08		0.20	39.00
KF0825B2SR		43.97	0.23			3500	0.15	3.60	0.18	34.80			
KF0825-2H	B,N,H,S	37.40	0.17			3000	0.11	2.64	0.13	30.90			
KF0825-2M	B,N,H,S	30.60	0.12			2500	0.08	1.92	0.10	25.80			
KF0825-2L	B,N,H,S	24.20	0.08			2000	0.06	1.44	0.07	22.30			
KF0825-2E	B,N,H,S	18.44	0.05			1500	0.04	0.96	0.05	20.50			
KF0825B4UR	B	48	40.8 ~ 55.2			50.25	0.30	4000	0.13	6.24		0.16	39.00
KF0825B4SR						43.97	0.23	3500	0.10	4.80		0.12	34.80
KF0825B4HR				37.40	0.17	3000	0.07	3.36	0.08	30.90			
KF0825B4MR				30.60	0.12	2500	0.05	2.40	0.06	25.80			
KF0825B4LR				24.20	0.08	2000	0.03	1.44	0.04	22.30			

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

