

80X80X20 mm

KF0820-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0820-1URAJ	B	12	10.2 ~ 13.8	52.51	0.313	5000	0.30	3.60	0.30	47.8	61
KF0820-1UR	B,N,H			41.87	0.223	4000	0.27	3.24	0.30	39.6	
KF0820-1SR	B,N,H,S			36.55	0.178	3500	0.20	2.40	0.22	35.5	
KF0820-1H	B,N,H,S			31.09	0.135	3000	0.14	1.68	0.15	31.4	
KF0820-1M	B,N,H,S			25.75	0.097	2500	0.08	0.96	0.09	26.5	
KF0820-1L	B,N,H,S			20.44	0.065	2000	0.06	0.72	0.07	21.3	
KF0820-1E	B,N,H,S			15.20	0.039	1500	0.04	0.48	0.05	14.2	
KF0820-2UR	B,N,H	24	20.4 ~ 27.6	41.87	0.223	4000	0.13	3.12	0.15	39.6	
KF0820-2SR	B,N,H,S			36.55	0.178	3500	0.10	2.40	0.11	35.5	
KF0820-2H	B,N,H,S			31.09	0.135	3000	0.07	1.68	0.08	31.4	
KF0820-2M	B,N,H,S			25.75	0.097	2500	0.06	1.44	0.07	26.5	
KF0820-2L	B,N,H,S			20.44	0.065	2000	0.04	0.96	0.05	21.3	
KF0820-2E	B,N,H,S			15.20	0.039	1500	0.03	0.72	0.04	14.2	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

