

80X80X15 mm

JF0815-03 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0815-1URAE	B	12	10.2 ~ 13.8	47.00	0.225	4500	0.34	4.08	0.34	40.8	49
JF0815-1UR	B,N,H			41.75	0.185	4000	0.31	3.72	0.34	38.0	
JF0815-1SR	B,N,H,S			36.50	0.145	3500	0.20	2.40	0.22	35.2	
JF0815-1H	B,N,H,S			31.22	0.111	3000	0.15	1.80	0.17	30.3	
JF0815-1M	B,N,H,S			25.79	0.081	2500	0.10	1.20	0.11	25.6	
JF0815-1L	B,N,H,S			20.73	0.053	2000	0.05	0.60	0.06	21.6	
JF0815-2URAB	B	24	20.4 ~ 27.6	43.85	0.201	4200	0.17	4.08	0.17	39.1	
JF0815-2UR	B,N,H			41.75	0.185	4000	0.15	3.60	0.17	38.0	
JF0815-2SR	B,N,H			36.50	0.145	3500	0.11	2.64	0.14	35.2	
JF0815-2H	B,N,H,S			31.22	0.111	3000	0.09	2.16	0.10	30.3	
JF0815-2M	B,N,H,S			25.79	0.081	2500	0.06	1.44	0.07	25.6	
JF0815-2L	B,N,H,S			20.73	0.053	2000	0.05	1.20	0.06	21.6	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

