

80X80X10 mm

DF0810-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
DF0810-5SR	B	5	4.25~5.75	27.17	0.099	3500	0.45	2.25	0.45	34.5	35
DF0810-5HR				23.18	0.072	3000	0.25	1.25	0.25	29.3	
DF0810-5MR				19.21	0.051	2500	0.20	1.00	0.20	24.2	
DF0810-5LR				15.60	0.035	2000	0.16	0.80	0.16	21.1	
DF0810-1HR		12	10.2~13.8	23.18	0.072	3000	0.28	3.36	0.34	29.3	
DF0810-1MR				19.21	0.051	2500	0.18	2.16	0.28	24.2	
DF0810-1LR				15.60	0.035	2000	0.14	1.68	0.20	21.1	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

