

DC AXIAL FAN

JAMICON®

70X70X15 mm

KF0715-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0715-1SR	B,N,H	12	10.2~13.8	40.45	0.238	5000	0.35	4.20	0.41	41.3	49
KF0715-1HR	B,N,H,S			34.05	0.174	4200	0.30	3.60	0.33	37.1	
KF0715-1M	B,N,H,S			29.16	0.134	3600	0.19	2.28	0.21	32.7	
KF0715-1L	B,N,H,S			24.00	0.093	3000	0.12	1.44	0.14	28.2	
KF0715-2SR	B	24	20.4~27.6	40.45	0.238	5000	0.25	6.00	0.28	41.3	
KF0715-2HR	B,N,H,S			34.05	0.174	4200	0.14	3.36	0.18	37.1	
KF0715-2M	B,N,H,S			29.16	0.134	3600	0.09	2.16	0.12	32.7	
KF0715-2L	B,N,H,S			24.00	0.093	3000	0.06	1.44	0.08	28.2	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

