

60X60X25 mm

JF0625-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0625B1TRAL	B	12	10.2 ~ 13.8	35.70	0.509	7200	0.38	4.56	0.38	46.9	59
JF0625B1TR	B			29.77	0.401	6000	0.37	4.44	0.38	42.1	
JF0625-1UR	B,N,H			27.17	0.338	5500	0.29	3.48	0.30	40.1	
JF0625-1S	B,N,H,S			24.12	0.263	5000	0.22	2.64	0.22	37.2	
JF0625-1H	B,N,H,S			21.56	0.215	4500	0.20	2.40	0.23	34.5	
JF0625-1M	B,N,H,S			19.15	0.172	4000	0.16	1.92	0.20	30.5	
JF0625-1L	B,N,H,S			16.78	0.134	3500	0.13	1.56	0.17	27.4	
JF0625-1E	B,N,H,S			14.26	0.097	3000	0.11	1.32	0.11	23.1	
JF0625-1V	B,N,H,S			11.84	0.070	2500	0.08	0.96	0.08	20.1	
JF0625B2TRAJ	B	24	20.4 ~ 27.6	34.71	0.491	7000	0.21	5.04	0.21	46.1	
JF0625B2TR	B			29.77	0.401	6000	0.20	4.80	0.21	42.1	
JF0625-2UR	B,N,H			27.17	0.338	5500	0.16	3.84	0.16	40.1	
JF0625-2S	B,N,H			24.12	0.263	5000	0.13	3.12	0.14	37.2	
JF0625-2H	B,N,H,S			21.56	0.215	4500	0.12	2.88	0.17	34.5	
JF0625-2M	B,N,H,S			19.15	0.172	4000	0.11	2.64	0.13	30.5	
JF0625-2L	B,N,H,S			16.78	0.134	3500	0.10	2.40	0.12	27.4	
JF0625-2E	B,N,H,S			14.26	0.097	3000	0.07	1.68	0.07	23.1	
JF0625-2V	B,N,H,S			11.84	0.070	2500	0.06	1.44	0.06	20.1	
Jf0625-4UR	B,N,H	48	40.8 ~ 55.2	27.17	0.338	5500	0.11	5.28	0.11	40.1	
Jf0625-4SR	B,N,H			24.12	0.263	5000	0.09	4.32	0.09	37.2	
Jf0625-4HR	B,N,H,S			21.56	0.215	4500	0.07	3.36	0.08	34.5	
Jf0625-4MR	B,N,H,S			19.15	0.172	4000	0.06	2.88	0.07	30.5	
Jf0625-4LR	B,N,H,S			16.78	0.134	3500	0.05	2.40	0.06	27.4	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

