

60X60X20 mm

JF0620-00 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF0620B1UR	B	12	10.2 ~ 13.8	19.11	0.291	5500	0.19	2.28	0.20	35.9	50
JF0620-1SR	B,N,S			17.41	0.247	5000	0.17	2.04	0.18	32.8	
JF0620-1H	B,N,S			15.56	0.196	4500	0.15	1.80	0.17	29.4	
JF0620-1M	B,N,S			13.84	0.157	4000	0.13	1.56	0.15	26.4	
JF0620-1L	B,N,S			12.06	0.127	3500	0.10	1.20	0.13	23.6	
JF0620-1E	B,N,S			10.13	0.090	3000	0.09	1.08	0.09	20.3	
JF0620-1V	B,N,S			8.48	0.068	2500	0.07	0.84	0.07	17.1	
JF0620B2UR	B	24	20.4 ~ 27.6	19.11	0.291	5500	0.12	2.88	0.13	35.9	
JF0620-2S	B,N,S			17.41	0.247	5000	0.10	2.40	0.11	32.8	
JF0620-2H	B,N,S			15.56	0.196	4500	0.09	2.16	0.13	29.4	
JF0620-2M	B,N,S			13.84	0.157	4000	0.08	1.92	0.11	26.4	
JF0620-2L	B,N,S			12.06	0.127	3500	0.07	1.68	0.07	23.6	
JF0620-2E	B,N,S			10.13	0.090	3000	0.06	1.44	0.06	20.3	
JF0620-2V	B,N,S			8.48	0.068	2500	0.05	1.20	0.05	17.1	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

