

DC AXIAL FAN

JAMICON®

60X60X20 mm

KF0620-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0620-1SRAO	B	12	10.2 ~ 13.8	37.00	0.457	6500	0.38	4.56	4.8	48.2	43
KF0620-1SR	B,N,H			28.27	0.289	5000	0.38	4.56	4.8	39.2	
KF0620-1HR	B,N,H,S			25.36	0.233	4500	0.25	3.00	3.2	36.2	
KF0620-1M	B,N,H,S			22.40	0.186	4000	0.20	2.40	2.5	32.4	
KF0620-1L	B,N,H,S			19.45	0.142	3500	0.14	1.68	1.7	27.8	
KF0620-1E	B,N,H,S			16.66	0.105	3000	0.10	1.20	1.3	25.2	
KF0620-1V	B,N,H,S			13.82	0.072	2500	0.07	0.84	0.9	20.7	
KF0620-2SR	B,N,H	24	20.4 ~ 27.6	28.27	0.289	5000	0.21	5.04	5.1	39.2	
KF0620-2H	B,N,H,S			25.36	0.233	4500	0.14	3.36	3.5	36.2	
KF0620-2M	B,N,H,S			22.40	0.186	4000	0.12	2.88	3.1	32.4	
KF0620-2L	B,N,H,S			19.45	0.142	3500	0.10	2.40	2.5	27.8	
KF0620-2E	B,N,H,S			16.66	0.105	3000	0.07	1.68	1.7	25.2	
KF0620-2V	B,N,H,S			13.82	0.072	2500	0.04	0.96	1.2	20.7	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

