

DC AXIAL FAN

JAMICON®

60X60X15 mm

KF0615-02 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0615-5MR	B,N,H	5	4.25~5.75	18.78	0.14	4000	0.42	2.10	2.4	30.0	36
KF0615-5L	B,N,H,S			16.33	0.11	3500	0.23	1.15	1.3	26.9	
KF0615-5E	B,N,H,S			13.83	0.08	3000	0.16	0.80	0.9	22.8	
KF0615-5V	B,N,H,S			11.21	0.06	2500	0.10	0.50	0.6	21.5	
KF0615-1UR	B,N,H	12	10.2~13.8	26.54	0.26	5500	0.24	2.88	3.1	39.7	
KF0615-1S				24.40	0.22	5000	0.20	2.40	2.5	35.7	
KF0615-1H	B,N,H,S			21.35	0.18	4500	0.19	2.28	2.3	33.1	
KF0615-1M	B,N,H,S			18.78	0.14	4000	0.15	1.80	1.9	30.0	
KF0615-1L	B,N,H,S			16.33	0.11	3500	0.10	1.20	1.3	26.9	
KF0615-1E	B,N,H,S			13.83	0.08	3000	0.08	0.96	1.0	22.8	
KF0615-1V	B,N,H,S			11.21	0.06	2500	0.06	0.72	0.8	21.5	
KF0615-2UR	B,N,H	24	20.4~27.6	26.54	0.26	5500	0.18	4.32	4.6	39.7	
KF0615-2S				24.40	0.22	5000	0.15	3.60	3.7	35.7	
KF0615-2H	B,N,H,S			21.35	0.18	4500	0.12	2.88	3.0	33.1	
KF0615-2M	B,N,H,S			18.78	0.14	4000	0.09	2.16	2.3	30.0	
KF0615-2L	B,N,H,S			16.33	0.11	3500	0.07	1.68	1.7	26.9	
KF0615-2E	B,N,H,S			13.83	0.08	3000	0.05	1.20	1.4	22.8	
KF0615-2V	B,N,H,S			11.21	0.06	2500	0.04	0.96	1.2	21.5	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

