

50X50X10 mm

KF0510-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)	
KF0510B5H	B	5	4.25~5.75	13.04	0.138	5200	0.22	1.10	1.1	29.0	17	
KF0510B5M				11.23	0.108	4500	0.14	0.70	0.9	26.2		
KF0510B5L				8.72	0.068	3500	0.09	0.45	0.6	21.2		
KF0510-5H	N,S			13.04	0.138	5200	0.23	1.15	1.1	29.0		
KF0510-5M				11.23	0.108	4500	0.15	0.75	1.1	26.2		
KF0510-5L				8.72	0.068	3500	0.10	0.50	0.7	21.2		
KF0510B1H-AH	B	12	10.2~13.8	14.70	0.150	6000	0.11	1.32	1.6	32.2		
KF0510B1H				13.04	0.138	5200	0.11	1.32	1.6	29.0		
KF0510B1M				11.23	0.108	4500	0.066	0.80	0.8	26.2		
KF0510B1L				8.72	0.068	3500	0.05	0.60	0.7	21.2		
KF0510-1H	N,S			13.04	0.138	5200	0.12	1.44	1.9	29.0		
KF0510-1M				11.23	0.108	4500	0.083	1.00	1.0	26.2		
KF0510-1L				8.72	0.068	3500	0.06	0.72	0.8	21.2		
KF0510B2H-AH				B	24	20.4~27.6	14.70	0.150	6000	0.06		1.44
KF0510B2H	13.04	0.138	5200				0.06	1.44	1.7	29.0		
KF0510B2M	11.23	0.108	4500				0.05	1.20	1.5	26.2		
KF0510B2L	8.72	0.068	3500				0.04	0.96	1.3	21.2		
KF0510-2H	N,S	13.04	0.138				5200	0.06	1.44	1.7		29.0
KF0510-2M		11.23	0.108				4500	0.05	1.20	1.5		26.2
KF0510-2L		8.72	0.068	3500			0.04	0.96	1.3	21.2		

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

