

DC AXIAL FAN

JAMICON®

40X40X28 mm

KF0428-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0428B1UR	B	12	10.2~13.8	24.34	1.177	14000	0.64	7.68	0.71	54.10	40
KF0428B1SR				22.43	0.980	13000	0.51	6.12	0.61	52.30	
KF0428B1HR				18.55	0.728	11000	0.29	3.48	0.35	46.90	
KF0428B1MR				16.07	0.543	9500	0.20	2.40	0.24	43.70	
KF0428B1LR				13.39	0.395	8000	0.16	1.92	0.19	40.90	
KF0428B1ER				11.49	0.304	7000	0.12	1.44	0.14	34.80	
KF0428B1VR				8.16	0.168	5000	0.06	0.72	0.07	24.90	
KF0428B2LR	B	24	20.4~27.6	13.39	0.395	8000	0.11	2.64	0.13	40.90	
KF0428B2ER				11.49	0.304	7000	0.09	2.16	0.11	34.80	
KF0428B2VR				8.16	0.168	5000	0.05	1.20	0.06	24.90	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

