

DC AXIAL FAN

JAMICON®

40X40X20 mm

KF0420-01
KF0420-04 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0420B5H-AJ	B	5	4.25~5.75	10.91	0.386	8500	0.24	1.20	1.3	35.2	25
KF0420-5H	B,N,S			9.50	0.296	7500	0.23	1.15	1.3	32.6	
KF0420-5M	B,N,S			7.73	0.204	6200	0.15	0.75	0.8	26.5	
KF0420-5L	B,N,S			6.24	0.134	5000	0.09	0.45	0.6	22.0	
KF0420B1H-AO	B	12	10.2~13.8	11.62	0.431	9000	0.13	1.56	1.6	36.5	
KF0420B1H-AJ	B			10.91	0.386	8500	0.13	1.56	1.6	35.2	
KF0420-1H	B,N,S			9.50	0.296	7500	0.10	1.20	1.6	32.6	
KF0420-1M	B,N,S			7.73	0.204	6200	0.08	0.96	1.3	26.5	
KF0420-1L	B,N,S			6.24	0.134	5000	0.06	0.72	0.8	22.0	
KF0420B2S-AE	B	24	20.4~27.6	11.62	0.431	9000	0.10	2.40	2.6	36.5	
KF0420B2S	B			10.91	0.386	8500	0.09	2.16	2.6	35.2	
KF0420-2H	B,N,S			9.50	0.296	7500	0.07	1.68	2.0	32.6	
KF0420-2M	B,N,S			7.73	0.204	6200	0.05	1.20	1.5	26.5	
KF0420-2L	B,N,S			6.24	0.134	5000	0.04	0.96	1.1	22.0	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

