

DC AXIAL FAN

JAMICON®

40X40X15 mm

KF0415-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0415B5SR	B	5	4.25~5.75	10.32	0.325	8600	0.53	2.65	0.70	39.0	25
KF0415B5HR				8.84	0.237	7300	0.32	1.60	0.44	32.9	
KF0415-5M	B,N,S			7.14	0.159	6000	0.21	1.05	0.25	28.6	
KF0415-5L	B,N,S			5.70	0.113	5000	0.16	0.80	0.17	24.9	
KF0415B1SRAR	B	12	10.2~13.8	14.94	0.537	12200	0.23	2.76	0.25	53.1	
KF0415B1SR				10.32	0.325	8600	0.19	2.28	0.25	39.0	
KF0415B1HR	8.84			0.237	7300	0.13	1.56	0.17	32.9		
KF0415-1M	B,N,S			7.14	0.159	6000	0.08	0.96	0.11	28.6	
KF0415-1L	B,N,S			5.70	0.113	5000	0.06	0.72	0.08	24.9	
KF0415B2SRAN	B	24	20.4~27.6	11.05	0.435	10000	0.09	2.16	0.11	45.6	
KF0415B2SR				10.32	0.325	8600	0.09	2.16	0.11	39.0	
KF0415B2HR	8.84			0.237	7300	0.07	1.68	0.08	32.9		
KF0415-2M	B,N,S			7.14	0.159	6000	0.05	1.20	0.06	28.6	
KF0415-2L	B,N,S			5.70	0.113	5000	0.03	0.72	0.04	24.9	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

