

DC AXIAL FAN

JAMICON®

30X30X10 mm

KF0310-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 15\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0310B5HR	B	5	4.25~5.75	3.93	0.212	10000	0.20	1.00	1.0	31.6	8.5
KF0310B5MR				3.34	0.155	8500	0.16	0.80	0.9	27.4	
KF0310B5LR				2.35	0.080	6000	0.08	0.40	0.5	20.1	
KF0310-5HR	N,S			3.93	0.212	10000	0.20	1.00	1.1	31.6	
KF0310-5MR				3.34	0.155	8500	0.16	0.80	1.0	27.4	
KF0310-5LR				2.35	0.080	6000	0.09	0.40	0.6	20.1	
KF0310B1HR	B	12	10.2~13.8	3.93	0.212	10000	0.11	1.32	1.4	31.6	
KF0310B1MR				3.34	0.155	8500	0.08	0.96	1.3	27.4	
KF0310B1LR				2.35	0.080	6000	0.058	0.70	0.7	20.1	
KF0310-1HR	N,S			3.93	0.212	10000	0.09	1.08	1.5	31.6	
KF0310-1MR				3.34	0.155	8500	0.06	0.72	1.3	27.4	
KF0310-1LR				2.35	0.080	6000	0.04	0.48	0.7	20.1	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

