

## 40x40x20mm

## SF0420-33 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

### SPECIFICATIONS

| Model     | Bearing | Rated Voltage (V) | Operating Voltage (V) | Air Flow (CFM) | Static Pressure (inchH <sub>2</sub> O) | Speed (R.P.M.) | Input Current (Amp) | Input Power (Watt) | Nominal Current (Amp) | Noise (dBA) | Weight (g) |
|-----------|---------|-------------------|-----------------------|----------------|----------------------------------------|----------------|---------------------|--------------------|-----------------------|-------------|------------|
| SF0420-1M | N       | 12                | 10.2~13.8             | 13.71          | 0.676                                  | 10000          | 0.21                | 2.52               | 0.22                  | 42.8        | 25.6       |
| SF0420-1L | N       |                   |                       | 10.95          | 0.436                                  | 8000           | 0.13                | 1.56               | 0.18                  | 34.1        |            |
| SF0420-1E | N       |                   |                       | 8.88           | 0.300                                  | 6500           | 0.10                | 1.20               | 0.14                  | 29.7        |            |
| SF0420-1V | N       |                   |                       | 6.63           | 0.181                                  | 5000           | 0.06                | 0.72               | 0.10                  | 22.2        |            |
| SF0420-1M | N       | 24                | 20.4~27.6             | 13.71          | 0.676                                  | 10000          | 0.10                | 2.40               | 0.11                  | 42.8        |            |
| SF0420-1L | N       |                   |                       | 10.95          | 0.436                                  | 8000           | 0.07                | 1.68               | 0.09                  | 34.1        |            |
| SF0420-1E | N       |                   |                       | 8.88           | 0.300                                  | 6500           | 0.05                | 1.20               | 0.07                  | 29.7        |            |
| SF0420-1V | N       |                   |                       | 6.63           | 0.181                                  | 5000           | 0.04                | 0.96               | 0.05                  | 22.2        |            |

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

