

DC AXIAL FAN

JAMICON®

120X120X25 mm

SF1225-11 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
SF1225-1U	B	12	10.2~13.8	133.19	0.294	3600	0.60	7.20	0.90	46.7	150
SF1225-1S	B			116.93	0.237	3100	0.38	4.56	0.45	42.3	
SF1225-1H	B			98.06	0.174	2600	0.23	2.76	0.35	38.6	
SF1225-1M	B			79.15	0.122	2100	0.13	1.56	0.25	34.3	
SF1225-1L	B			59.46	0.073	1600	0.08	0.96	0.15	28.7	
SF1225-2U	B	24	20.4~27.6	133.19	0.294	3600	0.29	6.96	0.50	46.7	
SF1225-2S	B			116.93	0.237	3100	0.18	4.32	0.25	42.3	
SF1225-2H	B			98.06	0.174	2600	0.13	3.12	0.20	38.6	
SF1225-2M	B			79.15	0.122	2100	0.07	1.68	0.15	34.3	
SF1225-2L	B			59.46	0.073	1600	0.04	0.96	0.10	28.7	

Specifications subject to change without notice

All models could be customized or are not listed above, please contact us.

B= Dual Ball bearing / N= NOVA -SLEEVE bearing / H= HTLS bearing / S= Sleeve bearing

JAMICON FAN PERFORMANCE CURVES

Air Flow (CMM) (M³/m)

